

COMPRESOR TORNILLO LUBRICADO 10HP

DESCRIPCIÓN TÉCNICA

Model		SCR10M-8	SCR10M-10
Capacity/ Pressure (cfm. psi)		36/115	34/145
MOTOR	Power(KW)	7.5KW(10HP)	
	Speed(r/min)	3530	
	Starting way	Direct Starting	
	Volt(V)	220/380/440	
	Motor safety grade	IP54	
	Motor isolation grade	F	
Electrical Supply		220V/60HZ/3Phase	
Outlet Temperature (C°)		≤ Enviroment Temperature +8°C	
Drive Way		Belt	
Noise level at 1 meter		68+- 3dB	
Cooled method		Air cooling	
Oil content		1~3 ppm	
Outlet Connection		1/2" NPT	
Dimension	Length(mm)	900	
	Width(mm)	680	
	Height(mm)	970	
Weight (Kg.)		250	

COMPRESOR TORNILLO LUBRICADO 15 HP

DESCRIPCIÓN TÉCNICA

Model		SCR15M-8	SCR15M-10
Capacity/ Pressure (cfm. psi)		53/115	46/145
MOTOR	Power(KW)	11KW(15HP)	
	Speed(r/min)	3535	
	Starting way	Y – Δ Starting	
	Volt(V)	220/380/440	
	Motor safety grade	IP54	
	Motor isolation grade	F	
Electrical Supply		220V/60HZ/3Phase	
Outlet Temperature (C°)		≤ Enviroment Temperature +8°C	
Drive Way		Belt	
Noise level at 1 meter		68+- 3dB	
Cooled method		Air cooling	
Oil content		1~3 ppm	
Outlet Connection		3/4" NPT	
Dimension	Length(mm)	950	
	Width(mm)	800	
	Height(mm)	1130	
Weight (Kg.)		380	

COMPRESOR TORNILLO LUBRICADO 20 HP

DESCRIPCIÓN TÉCNICA

Model		SCR20M-8	SCR20M-10
Capacity/ Pressure (cfm. psi)		78/115	68/145
MOTOR	Power(KW)	15KW(20HP)	
	Speed(r/min)	3535	
	Starting way	Y – Δ Starting	
	Volt(V)	220/380/440	
	Motor safety grade	IP54	
	Motor isolation grade	F	
Electrical Supply		220V/60HZ/3Phase	
Outlet Temperature (C°)		≤ Enviroment Temperature +8°C	
Drive Way		Belt	
Noise level at 1 meter		68+ 3dB	
Cooled method		Air cooling	
Oil content		1~3 ppm	
Outlet Connection		3/4" NPT	
Dimension	Length(mm)	950	
	Width(mm)	800	
	Height(mm)	1130	
Weight (Kg.)		420	

COMPRESOR TORNILLO LUBRICADO 20 HP

DESCRIPCIÓN TÉCNICA

Model		SCR20M-12
Capacity/ Pressure (cfm. psi)		45/174
MOTOR	Power(KW)	15KW(20HP)
	Speed(r/min)	2800
	Starting way	Y – Δ Starting
	Volt(V)	220/440
	Motor safety grade	IP54
	Motor isolation grade	F
Electrical Supply		220V/60HZ/3Phase
Outlet Temperature (C°)		≤ Enviroment Temperature +8°C
Drive Way		Belt
Noise level at 1 meter		68+ 3dB
Cooled method		Air cooling
Oil content		1~3 ppm
Outlet Connection		3/4" NPT
Dimension	Length(mm)	950
	Width(mm)	800
	Height(mm)	1130
Weight (Kg.)		420

COMPRESOR TORNILLO LUBRICADO 25 HP

DESCRIPCIÓN TÉCNICA

Model		SCR25M-8	SCR25M-10
Capacity/ Pressure (cfm. psi)		103/115	85/145
MOTOR	Power(KW)	18.5KW(25HP)	
	Speed(r/min)	3535	
	Starting way	Y – Δ Starting	
	Volt(V)	220/380/440	
	Motor safety grade	IP54	
	Motor isolation grade	F	
Electrical Supply		440V/60HZ/3Phase	
Outlet Temperature (C°)		≤ Enviroment Temperature +8°C	
Drive Way		Belt	
Noise level at 1 meter		70+2dB	
Cooled method		Air cooling	
Oil content		1~3 ppm	
Outlet Connection		1" NPT	
Dimension	Length(mm)	1150	
	Width(mm)	900	
	Height(mm)	1350	
Weight (Kg.)		560	

COMPRESOR TORNILLO LUBRICADO 30 HP

DESCRIPCIÓN TÉCNICA

Model		SCR30M-8	SCR30M-10
Capacity/ Pressure (cfm. psi)		128/115	114/145
MOTOR	Power(KW)	22KW(30HP)	
	Speed(r/min)	3535	
	Starting way	Y – Δ Starting	
	Volt(V)	220/380/440	
	Motor safety grade	IP54	
	Motor isolation grade	F	
Electrical Supply		220V/60HZ/3Phase	
Outlet Temperature (C°)		≤ Enviroment Temperature +8°C	
Drive Way		Direct	
Noise level at 1 meter		70+2dB	
Cooled method		Air cooling	
Oil content		1~3 ppm	
Outlet Connection		1" NPT	
Dimension	Length(mm)	1150	
	Width(mm)	900	
	Height(mm)	1350	
Weight (Kg.)		580	

COMPRESOR TORNILLO LUBRICADO 40 HP

DESCRIPCIÓN TÉCNICA



Model		SCR40M-8	SCR40M-10
Capacity/ Pressure (cfm. psi)		163/115	152/145
MOTOR	Power(KW)	30KW(40HP)	
	Speed(r/min)	2979	
	Starting way	Y – Δ Starting	
	Volt(V)	220/380/440	
	Motor safety grade	IP54	
	Motor isolation grade	F	
Electrical Supply		220V/60HZ/3Phase	
Outlet Temperature (C°)		≤ Enviroment Temperature +8°C	
Drive Way		Direct	
Noise level at 1 meter		70+2dB	
Cooled method		Air cooling	
Oil content		1~3 ppm	
Outlet Connection		1" NPT	
Dimension	Length(mm)	1150	
	Width(mm)	900	
	Height(mm)	1350	
Weight (Kg.)		640	

COMPRESOR TORNILLO LUBRICADO 50 HP

DESCRIPCIÓN TÉCNICA

Model		SCR50D-8	SCR50D-10
Capacity/ Pressure (cfm. psi)		212/116	200/145
MOTOR	Power(KW)	37KW(50HP)	
	Speed(r/min)	2979	
	Starting way	Y – Δ Starting	
	Volt(V)	380/440	
	Motor safety grade	IP54	
	Motor isolation grade	F	
Electrical Supply		440V/60HZ/3Phase	
Outlet Temperature (C°)		≤ Enviroment Temperature +8°C	
Drive Way		Direct	
Noise level at 1 meter		70+2dB	
Cooled method		Air cooling	
Oil content		1~3 ppm	
Outlet Connection		1 1/2" NPT	
Dimension	Length(mm)	1000	
	Width(mm)	1600	
	Height(mm)	1360	
Weight (Kg.)		860	

COMPRESOR TORNILLO LUBRICADO 60 HP (TRANSMISIÓN DIRECTA)

DESCRIPCIÓN TÉCNICA



Model		SCR60D-8	SCR60D-10
Capacity/ Pressure (cfm. psi)		265/115	251/145
MOTOR	Power(KW)	45KW(60HP)	
	Speed(r/min)	2979	
	Starting way	Y – Δ Starting	
	Volt(V)	440	
	Motor safety grade	IP54	
	Motor isolation grade	F	
Electrical Supply		220V/60HZ/3Phase	
Outlet Temperature (C°)		≤ Enviroment Temperature +8°C	
Drive Way		Direct	
Noise level at 1 meter		70+2dB	
Cooled method		Air cooling	
Oil content		1~3 ppm	
Outlet Connection		1 1/2" NPT	
Dimension	Length(mm)	1000	
	Width(mm)	1820	
	Height(mm)	1360	
Weight (Kg.)		950	

COMPRESOR TORNILLO LUBRICADO 60 HP (CON FAJAS)

DESCRIPCIÓN TÉCNICA



Model		SCR 60M-8	SCR60M-10
Capacity/ Pressure (cfm. psi)		255/115	241/145
MOTOR	Power(KW)	45KW(60HP)	
	Speed(r/min)	2979	
	Starting way	Y – Δ Starting	
	Volt(V)	440	
	Motor safety grade	IP54	
	Motor isolation grade	F	
Electrical Supply		220V/60HZ/3Phase	
Outlet Temperature (C°)		≤ Environment Temperature +8°C	
Drive Way		Direct	
Noise level at 1 meter		70±2dB	
Cooled method		Air cooling	
Oil content		1~3 ppm	
Outlet Connection		1 1/2" NPT	
Dimension	Length(mm)	1300	
	Width(mm)	1000	
	Height(mm)	1470	
Weight (Kg.)		920	

COMPRESOR TORNILLO LUBRICADO 75 HP

DESCRIPCIÓN TÉCNICA

Model		SCR75D-8	SCR75D-10
Capacity/ Pressure (cfm. psi)		265/115	251/145
MOTOR	Power(KW)	55KW(75HP)	
	Speed(r/min)	3560	
	Starting way	Y – Δ Starting	
	Volt(V)	440	
	Motor safety grade	IP54	
	Motor isolation grade	F	
Electrical Supply		440V/60HZ/3Phase	
Outlet Temperature (C°)		≤ Enviroment Temperature +8°C	
Drive Way		Direct	
Noise level at 1 meter		70+-2dB	
Cooled method		Air cooling	
Oil content		1~3 ppm	
Outlet Connection		2" NPT	
Dimension	Length(mm)	1360	
	Width(mm)	2200	
	Height(mm)	1755	
Weight (Kg.)		1820	

COMPRESOR TORNILLO LUBRICADO 100 HP

DESCRIPCIÓN TÉCNICA



Model		SCR100D-8	SCR100D-10
Capacity/ Pressure (cfm. psi)		456/115	417/145
MOTOR	Power(KW)	75KW(100HP)	
	Speed(r/min)	3560	
	Starting way	Y – Δ Starting	
	Volt(V)	440	
	Motor safety grade	IP54	
	Motor isolation grade	F	
Electrical Supply		440V/60HZ/3Phase	
Outlet Temperature (C°)		≤ Enviroment Temperature +8°C	
Drive Way		Direct	
Noise level at 1 meter		72+2dB	
Cooled method		Air cooling	
Oil content		1~3 ppm	
Outlet Connection		2" NPT	
Dimension	Length(mm)	2200	
	Width(mm)	1360	
	Height(mm)	1755	
Weight (Kg.)		1860	

COMPRESOR TORNILLO LUBRICADO 120 HP

DESCRIPCIÓN TÉCNICA



Model		SCR120D-8	SCR120D-10
Capacity/ Pressure (cfm. psi)		596/116	516/145
MOTOR	Power(KW)	90KW(120HP)	
	Speed(r/min)	2970	
	Starting way	Y – Δ Starting	
	Volt(V)	440	
	Motor safety grade	IP54	
	Motor isolation grade	F	
Electrical Supply		440V/60HZ/3Phase	
Outlet Temperature (C°)		≤ Environment Temperature +8°C	
Drive Way		Direct	
Noise level at 1 meter		72+2dB	
Cooled method		Air cooling	
Oil content		1~3 ppm	
Outlet Connection		2" NPT	
Dimension	Length(mm)	1585	
	Width(mm)	2100	
	Height(mm)	1800	
Weight (Kg.)		1450	

COMPRESOR TORNILLO LUBRICADO 150 HP

DESCRIPCIÓN TÉCNICA

Model		SCR150D-8	SCR150D-10
Capacity/ Pressure (cfm. psi)		706/116	600/145
MOTOR	Power(KW)	110KW(150HP)	
	Speed(r/min)	2970	
	Starting way	Y – Δ Starting	
	Volt(V)	440	
	Motor safety grade	IP54	
	Motor isolation grade	F	
Electrical Supply		440V/60HZ/3Phase	
Outlet Temperature (C°)		≤ Enviroment Temperature +8°C	
Drive Way		Direct	
Noise level at 1 meter		75+2dB	
Cooled method		Air cooling	
Oil content		1~3 ppm	
Outlet Connection		2 1/2" NPT	
Dimension	Length(mm)	1348	
	Width(mm)	2400	
	Height(mm)	1800	
Weight (Kg.)		2700	